

Automatic Detection, and P- and S-wave Picking Algorithm: an application to the 2009 L'Aquila (Central Italy) earthquake sequence.

F. Aldersons<sup>1</sup>, L. Chiaraluce<sup>2</sup>, R. Di Stefano<sup>2</sup>, D. Piccinini<sup>3</sup> and L. Valoroso<sup>2</sup>.

<sup>1</sup> Scientific Consulting - Amman - Jordan fred@faldersons.net

<sup>2</sup> Centro Nazionale Terremoti – Istituto Nazionale di Geofisica e Vulcanologia

<sup>3</sup> Sismologia e Tettonofisica – Istituto Nazionale di Geofisica e Vulcanologia

In order to process as quickly as possible the enormous amount of digital waveforms continuously recorded at permanent and temporary seismic stations in Italy, we implemented a semi-automatic procedure in order to identify local earthquakes and to provide consistently-weighted P- and S-wave arrival times.

Local earthquake detection is obtained by a STA/LTA ratio-based algorithm applied to 3-component seismograms from individual stations. A minimum of 4 triggered stations are required to declare a seismic event. This setting proves to be extremely effective to detect a large number of very-low magnitude earthquakes ( $ML > 1.5$ ) with a small number of false alarms.

The automatic picking system Mannekenpix (Aldersons, 2004), originally working on vertical component data, has been expanded to tackle 3-component data. In order to increase the reliability of P-wave and S-wave picking, the system is now virtually capable of discriminating among noise samples, P-wave samples and S-wave samples. This Identification is performed by a C5 decision tree (Quinlan, 1993) derived from training data. Five groups of predicting variables are included: Energy, Polarization, Spectral Power, Skewness and Kurtosis. In addition, the SEDSL algorithm (Magotra et al., 1989) is also used as a predictor.

The picking procedure requires a preliminary calibration derived from a reference subset of high-quality manual picks. After calibration, the picking system is statistically able to mimic the picking by a human analyst and to provide consistent uncertainty estimates translated into picking weights.

We illustrate very satisfying results of the automatic procedure showing P- and S-phase automatic readings for the L'Aquila sequence. The readings are fully comparable to those of a good human analyst, allowing high-quality earthquake locations of low-magnitude events in an extremely short amount of time. For a full day of continuous recording, we obtain around 2600 triggers, from which 75% lead to high-quality located events (mean RMS 0.1s) with at least 25 phase readings.

## References

- Aldersons, F. (2004) Toward a Three-Dimensional Crustal Structure of the Dead Sea region from Local Earthquake Tomography. Ph.D. thesis, Tel Aviv University.
- Magotra, N., Ahmed, N. and Chael, E. (1989) Single-Station Seismic Event Detection and Location IEEE Transactions on Geoscience and Remote Sensing, 27, 1, 15-23.
- Quinlan, J.R. (1993) C 4.5: Programs for machine learning. The Morgan Kaufmann Series in Machine Learning, San Mateo, CA.